2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

5K-OEM

iKey

OEM Keyboard with Integrated HulaPoint II™

The 5K-OEM combines a 113-key keyboard with HulaPoint II[™], an upgraded p ointing device that offers improved sensitivity and increased durability, into a single, fully integrated unit. Each kit is comprised of an industrial silicone keypad, switch matrix board, keyboard controller and cables.



Technical Specifications		
Certifications	NEMA 4X UL60950, FCC Part 15 Class B	
Shock	3x11 ms pulses of 50g on each of 3 axes	
Cable	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 or AT/Serial Cable (providing separate keyboard and mouse connections), or Single-Cable USB	
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap	
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours	
Power	PS2: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB:85mA@5V (from CPU port)	
Compatability	PS/2 KEYBOARD/HULPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS	
Temperature Range	STORAGE: -40C to +70C OPERATING: -20C to +60C	
Weight	1.5 lbs (0.68 kg)	
Warranty	90 day limited warranty	
Humidity	100% (when properly installed)	
Dimensions	15.00" x 6.50" x 0.42" (w-h-d) 381.0mm x 165.1mm x 10.7mm	
Model Numbers		
Features and Benefits		
• 10-Key Numeric Pad		• 20 Function Keys
Integrated HulaPoint II Pointing Device		Silicone Rubber
• OFM		

• OEM

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800- 866-6506