

ADAM-4541

ADAM-4542+

ADAM-4561/4562



Multi-mode Fiber Optic to RS-232/422/485 Converter
Single-mode Fiber Optic to RS-232/422/485 Converter
1-port Isolated USB to RS-232/422/485 Converter



ADAM-4541



ADAM-4542+



ADAM-4561/4562

Specifications

General

- Power Input: Unregulated 10 ~ 30 V_{DC}
- Connectors: 1 x plug-in terminal block (#14 ~ 22 AWG) (RS-232/422/485)
2 x ST fiber connector
- Power Consumption: 1.5 W @ 24 V_{DC}
- Operation Modes: Support Point-to-Point, and Ring (half-duplex)

Fiber Optic Communications

- Optical Power Budget (Attenuation): 15 dB (measured with 62.5/125 μm)
- Transmission Distance: 2.5 km
- Transmission Mode: Multi mode (Send and Receive)
- Wavelength: 820 nm

Serial Communications

- Communication Mode: Asynchronous
- Speed Modes (bps): 1200, 2400, 4800, 9600, 19.2 k, 38.4 k, 57.6k, 115.2 k and RS-232/422 mode (switchable)
- Transmission Mode: Full/half duplex, bidirectional

Specifications

General

- Power Input: Unregulated 12 ~ 24 V_{DC}
- Connectors: 1 x plug-in terminal block (#14 ~ 22 AWG) (RS-232/422/485)
1 x SC fiber connector
- Power Consumption: 3 W @ 24 V_{DC}
- Operation Modes: Support Point-to-Point, Redundant and Ring (half-duplex)

Fiber Optic Communications

- Optical Power Budget (Attenuation): 15 dB
- Transmission Distance: 15 km
- Transmission Mode: Single mode (Send and Receive)
- Wavelength: 1310 nm

Serial Communications

- Communication Mode: Asynchronous
- Speed Modes (bps)*: 1200, 2400, 4800, 9600, 19.2 k, 38.4 k, 57.6 k, 115.2 k, 230.4 k, 460.8 k, 921.6 k and RS-232/422 mode (switchable)
- Transmission Modes: Full/half duplex, bidirectional

* The highest speed for RS-232 mode is 115.2 kbps

Specifications

General

- Connectors: Network: USB-type A connector (type A to type B cable provided)
Serial:
ADAM-4561: 1 x plug-in terminal (#14 ~ 22 AWG) (3-wire RS-232/422/485)
ADAM-4562: 1 x DB-9 serial connectors (9-wire RS-232)
- Isolation Voltage: ADAM-4561: 3,000 V_{DC}
ADAM-4562: 2,500 V_{DC}
- Power Consumption: ADAM-4561: 1.5 W @ 5 V
ADAM-4562: 1.1 W @ 5 V
- Driver Support: ADAM-4561/4562: Windows 2000/XP/Vista/7/8 (32&64-bit)
- USB Specification Compliance: ADAM-4561: USB 2.0
ADAM-4562: USB 2.0

Serial Communications

- Speed Modes (bps): ADAM-4561: 600 bps to 115.2 kbps
ADAM-4562: 75 bps to 115.2 kbps
- Transmission Modes: Full/half duplex, bidirectional

Common Specifications

Environment

- Operating Humidity: 5 ~ 95% RH
- Operating Temperature: ADAM-4541/4542+: -10 ~ 70°C (14 ~ 158°F)
ADAM-4561/4562: -10 ~ 70°C (14 ~ 158°F)
- Storage Temperature: -25 ~ 85°C (-13 ~ 185°F)

Ordering Information

- ADAM-4541: Multi-mode Fiber to RS-232/422/485 Converter
- ADAM-4542+: Single-mode Fiber to RS-232/422/485 Converter
- ADAM-4561: 1-port Isolated USB to RS-232/422/485 Converter
- ADAM-4562: 1-port Isolated USB to RS-232 Converter