

DP-88-OEM

Compact Industrial OEM Keyboard

The DP-88-OEM is a small-footprint keyboard that meets harsh use standards. It has 88 full-size keys with embedded notebook key functions. The DP-88-OEM is a perfect fit for industrial, kiosk or mobile computing needs. It is designed to meet NEMA 4X specifications when properly installed.



Technical Specifications

Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 4 ft coiled (1.2m)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: KEYBOARD: 50mA@5V (from Keyboard port) USB: 50mA@5V (from Keyboard port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB
Compatability	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C OPERATING: -40C to +70C
Weight	1 lb (0.45 kg)
Warranty	90 day limited warranty
Humidity	100% (when properly installed)
Dimensions	11.12" x 6.05" x 0.42" (w-h-d) 282.45mm x 153.67mm x 10.7mm