

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

www.ikey.com

## **DT-1000-NI**

## **Nonincendive Stainless Steel Keyboard**

iKey offers a full line of nonincendive keyboards and pointing devices. The n onincendive DT-1000-NI is a full-size desktop keyboard featuring a stainless steel case and a sealed industrial silicone rubber keypad. It has a Factory Mutual a pproval of Class I, Division II. These units do not require barriers and are ideal for harsh working conditions. Its 24 function keys and 10-key number pad allow for us er versatility. The DT-1000-NI is designed to meet NEMA 4X specifications, making it resistant to dust, dirt, water and corrosive liquids. All units ship with bulkhead cables.



## **Technical Specifications**

Certifications NEMA 4X UL60950, FCC Part 15 Class B Factory Mutual Class I, Division II

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: sing-cable on PS/2 or single-cable USB

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4 mm) ACTUATION FORCE: 7.03

oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INERFACE CABLE: 94 VO

Compatability PS/2: All Windows Operating Systems USB: All Windows and Macintosh Operating Systems

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 16.25" x 7.88" x 1.8" (w-h-d) 412.8mm x 200.2mm x 45.7mm

Model Numbers

## **Features and Benefits**

10-Key Numeric Pad
114-Key Functionality

24 Function Keys
PS/2 or USB configurations available