

DU-5K-OEM

OEM Keyboard with HulaPoint II™

The DU-5K-OEM features the integrated HulaPoint II™ pointing device, 24 function keys and a 10-key number pad. It is designed to meet NEMA 4X specifications when properly installed.



Technical Specifications

Certifications	NEMA 4X, CE UL60950, FCC Part 15, Class B
Shock	3 x 11 ms pulses of 50g on each of 3 axis
Cable	10' (3 m)
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. ACTUATION FORCE: 180g FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 50mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
Comptability	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +70C OPERATING: -20C to +60C
Weight	1.50 lbs (0.68 kg)
Warranty	90 day limited warranty
Humidity	100% Humidity Resistant
Dimensions	14.75" x 6.43" x 0.35" (w-h-d) 374.7mm x 163.3mm x 8.9mm
Model Numbers	DU-5K-OEM-PS2: With PS/2 cable DU-5K-OEM-USB: With USB cable

Features and Benefits

- 10-Key Numeric Pad
- Industrial Silicone Rubber Keypad
- Integrated HulaPoint II Pointing Device
- Meets NEMA 4X (IP65) Specifications
- PS/2 or USB configurations available