

DU-5K-TP2

Desktop Keyboard with Touchpad



The DU-5K-TP2 features an integrated Cirque extended temperature touchpad pointing device, with left and right-click mouse buttons underneath for additional ease of use. It is designed to meet NEMA 4X specifications. It has 116-key functionality, including 24 function keys. The mounting holes on the back further increase the unit's versatility.

Technical Specifications

Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: Greater Than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 6.35 oz +/- 1.06 oz (180g +/- 30g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: KEYBOARD: 40mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 50mA@5V (from CPU port)
Compatability	PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	14.94" x 6.63" x 1.81" (w-h-d) 379.5mm x 168.1mm x 45.9mm
Model Numbers	

Features and Benefits

- 24 Function Keys
- Polycarbonate Case with Mounting Holes
- USB and PS/2 configurations available