

HP-DT-NI

NONINCENDIVE INDUSTRIAL HULAPOINT II™ POINTING DEVICE



Now available to ship! The nonincendive HulaPoint II™ features an upgraded pointing device that offers improved sensitivity and increased durability. It combines the functionality of a mouse and the flexibility of a joystick in one convenient, small-footprint package. The HP-DT-NI carries a Factory Mutual approval of Class I, Division II. Housed in a sturdy stainless steel case, it provides pressure-sensitive feedback for positive motion control without requiring vigorous movement. The low-profile design contains no protruding parts that might break, and no moving elements to collect dust. With its completely sealed, NEMA 4X design, the HulaPoint II™ can withstand spills, washdowns, contaminants and the impacts of an industrial environment. The HP-DT-NI units do not require barriers and are ideal for harsh working conditions. All units ship with bulkhead cables. Features PS/2 or USB configurations available Stainless Steel *Product available to ship, as of September 5, 2018*

Product Code HP-DT-NI

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B Factory Mutual approval for Class I, Division II
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: single PS2 or USB cable
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
COMPATIBILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to 158F) OPERATING: -20C to +60C (-4F to 140F)
WEIGHT	1.25 lbs (0.68 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100%
DIMENSIONS	4.90" x 4.90" x 1.13" (w-h-d) 124.5mm x 124.5mm x 28.7mm
MODEL NUMBERS	HP-DT-NI-PS2: With PS/2 cable HP-DT-NI-USB: With USB cable