

## HP-PM-IS

INTRINSICALLY SAFE PANEL MOUNT HULAPOINT II™  
POINTING DEVICE



Now available to ship! iKey manufactures devices to reduce risk of failure in your hazardous areas. The intrinsically safe HP-PM-IS features the HulaPoint II™ pointing device that offers improved sensitivity and increased durability. The low-profile design contains no protruding parts that might break and no moving elements to collect dust. With its completely sealed NEMA 4X design, the HulaPoint II™ can withstand spills, washdowns, contaminants and the impacts of an industrial environment. The HP-PM-IS has a Factory Mutual approval for Class I, II and III, Division I, Groups C, D, E, F and G. Features: Intrinsically Safe for Hazardous Environments PS/2 configurations available Stainless Steel Bezel

### Product Code HP-PM-IS

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B Factory Mutual Class I, II and III, Division I, Groups C, D, E, F, and G
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 5 feet from keyboard to Bulkhead Connector DESIGN: PS/2
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
COMPATIBILITY	PS/2: All Windows Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to 158F) OPERATING: -20C to +60C (-4F to 140F)
WEIGHT	1.25 lbs (0.57 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	6.0" x 6.0" x 1.12" (w-h-d) 152.4mm x 152.4mm x 28.4mm
MODEL NUMBERS	HP-PM-IS: With PS/2 cable