

# Nuvo-5608VR Series

Intel® 6th-Gen Core™ i7/i5 Fanless Surveillance System with 8x PoE+, DIO, CAN bus and 2x 3.5" HDD Accommodation Supporting RAID 0/1



CE FC

## Key Features

- Supports Intel® 6th-Gen Core™ i7/ i5/ i3 LGA1151 socket-type processor
- 8x 802.3at PoE+ ports and 2x GbE ports
- 2x 3.5" HDD accommodation, support RAID 0/1 with over 24 TB capacity
- Dedicated HDD heat-spreader for optimized thermal performance
- 4x full-size mini-PCIe sockets with SIM support
- 4-CH isolated DI and 4-CH isolated DO
- 1x CAN 2.0 port
- 8~35V wide-range DC input with built-in ignition power control
- Patented damping brackets\* to withstand 1 Grms Vibration

\*R.O.C Patent No. M491752

## Introduction

Nuvo-5608VR is Neosys' latest fanless surveillance system designed for real-time video analysis and streaming. It incorporates 6th-Gen Core™ i CPU, IP camera connectivity and massive storage capacity for emerging intelligent surveillance/ security applications.

Featuring eight Gigabit PoE+ ports, Nuvo-5608VR provides sufficient bandwidth to collect high-definition video streams from IP cameras, while its 6th-Gen Core™ i7 CPU is capable of performing real-time video analytics. It accommodates two 3.5" hard drives with RAID 0/ 1 configuration to support more than 24 TB storage capacity for recording 8-CH, 1080p@H.264 video for over 3 months.

Neosys' patented damping-bracket is shipped with Nuvo-5608VR to protect the system against vibration in harsh environmental conditions.

Being a rugged surveillance platform, Nuvo-5608VR is equipped with dedicated HDD heat-spreaders to maintain adequate HDD operating temperature and along with extra features such as DIO, CAN bus and ignition control, Nuvo-5608VR is the perfect fit for both stationary and mobile surveillance applications.

## Specifications


System Core		Expansion Bus	
<b>Processor</b>	Supports 6th-Gen Intel® Core™ i7/ i5/ i3 LGA1151 CPU Intel® Core™ i7-6700 (8M Cache, 3.4/ 4.0 GHz, 65W TDP) Intel® Core™ i5-6500 (6M Cache, 3.2/ 3.6 GHz, 65W TDP) Intel® Core™ i3-6100 (3M Cache, 3.7 GHz, 51W TDP) Intel® Core™ i7-6700TE (8M Cache, 2.4/ 3.4 GHz, 35W TDP) Intel® Core™ i5-6500TE (6M Cache, 2.3/ 3.3 GHz, 35W TDP) Intel® Core™ i3-6100TE (4M Cache, 2.7 GHz, 35W TDP)	<b>mini-PCIe</b>	1x full-size mini-PCIe socket with panel-accessible SIM socket 1x full-size mini-PCIe socket with internal SIM socket (mux with mSATA) 2x full-size mini-PCIe sockets (USB signals only) with internal SIM sockets
<b>Chipset</b>	Intel® Q170 platform controller hub	<b>Power Supply</b>	<b>DC Input</b>
<b>Graphics</b>	Integrated Intel® HD graphics 530		1x 3-pin pluggable terminal block for 8~35VDC DC input (IGN/GND/V+)
<b>Memory</b>	Up to 32 GB DDR4-2133 SDRAM (two SODIMM slots)	<b>Remote Ctrl. &amp; Status Output</b>	1x 10-pin (2x5) wafer connector for remote on/off control and status LED output
<b>AMT</b>	Supports AMT 11.0	<b>Mechanical</b>	
<b>TPM</b>	Supports TPM 2.0	<b>Dimension</b>	240 mm (W) x 225 mm (D) x 98 mm (H)
<b>I/O Interface</b>		<b>Weight</b>	3.5 kg
<b>Ethernet port</b>	2x Gigabit Ethernet ports by Intel® I219 and I210	<b>Mounting</b>	Wall-mount with damping brackets
<b>PoE+</b>	8x IEEE 802.3at (25.5W) Gigabit PoE+ ports by Intel® I210, 120W total power budget*	<b>Environmental</b>	
<b>USB 3.1</b>	4x USB 3.1 ports via native XHCI controller	<b>Operating Temperature</b>	with 35W CPU -25°C ~ 70°C (with mSATA/ SSD) ** -10°C ~ 60°C (with 3.5" HDD) **/**
<b>USB 2.0</b>	4x USB 2.0 ports		with 65W CPU -25°C ~ 50°C (with mSATA/ SSD) ** -10°C ~ 60°C (with 3.5" HDD) **/**
<b>Video Port</b>	1x stacked VGA + DVI-D 2x DisplayPorts, supporting 4K2K resolution	<b>Storage Temperature</b>	-40°C ~ 85°C
<b>Serial Port</b>	2x software-programmable RS-232/ 422/ 485 ports (COM1 & COM3) 1x RS-232 port (COM2)	<b>Humidity</b>	10%~90% , non-condensing
<b>Isolated DIO</b>	4x isolated DI and 4x isolated DO	<b>Vibration</b>	Operating, 1 Grms, 5-500 Hz, 3 Axes (w/ HDD and damping bracket installed, according to IEC60068-2-64)
<b>CAN</b>	1x CAN 2.0 port	<b>Shock</b>	Operating, 30 Grms, Half-sine 11 ms Duration (w/ HDD and damping bracket installed, according to IEC60068-2-27)
<b>Audio</b>	1x Mic-in and 1x speaker-out	<b>EMC</b>	CE/ FCC Class A, according to EN 55032 & EN 55024
<b>Storage Interface</b>			
<b>SATA HDD</b>	2x internal SATA port for 3.5" HDD installation, supporting RAID 0/ 1		
<b>mSATA</b>	1x full-size mSATA port (mux with mini-PCIe)		

\* The total power budget for Nuvo-5608VR is related to input voltage. 120W total budget is available with 24 VDC input. When 12 VDC input is applied, the total power budget is limited to 100W.


\*\* Operating temperature is verified with 100% CPU loading and 100% HDD loading applied using Passmark® BurnInTest 8.0. For detail testing criteria, please contact Neosys Technology.

\*\*\* Depending on the HDD selected, users may encounter performance degradation in sequential disk write at low/high ambient temperature. No data integrity issue was observed in -10°C ~ 60°C operating temperature range.

## Appearance



## Dimensions



## Ordering Information

Model No.	Product Description
Nuvo-5608VR	Intel® 6th-Gen Core™ fanless surveillance system with 8x PoE+ Ports, DIO, CAN bus and 2x 3.5" HDD RAID

## Optional Accessories

PA-160W-OW	160W AC/DC power adapter 20V/8A;18AWGx4C/120cm; cord end terminals for terminal block, operating temperature : -30 to 70 °C.
PA-280W-ET2	280W AC/DC power adapter 24V/11.67A;16AWG/100cm; cord end terminals for terminal block, operating temperature : -30 to 60 °C.