2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

PM-101

iKey

Full-Size Panel Mount Keyboard

iKey's SlimKey[™] PM-101 panel mount keyboard provides full-sized versatility in a r ugged, compact design. When properly installed, the PM-101 is engineered for NEMA 4X protaction from dust, water and corrosive liquids. It is designed for easy integration into workstations, kiosks and industrial environments. The large numeric pad on the PM-101 allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions.



Technical Specifications Certifications NEMA 4X, CE UL 60950, FCC Part 15 Class B Shock 3 X 11 ms pulses of 50g on each of 3 axes Cable LENGTH: 10' straight (3 m) DESIGN: "Y" PS/2 or USB Cable Key Switch MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap Vibration POWER SPECTRAL DENSITY: .04g^2/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER Vibration AXIS: 3 hours Power PS2: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port) Compatability PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS **Temperature Range** STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F) Weight 1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg) Warranty 1 Year Limited Warranty Humidity 100% Humidity Resistant Dimensions 15.10" x 6.05" x 0.58" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) Model Numbers PM-101-PS2: With PS/2 cable PM-101-USB: With USB cable **Features and Benefits**

ABS Polycarbonate Frame	Cleanable, Liquidproof Design
Industrial Silicone Rubber Keypad	PS/2 or USB configurations available

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800- 866-6506