

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

www.ikey.com

PM-65-TP-SS

Panel Mount Stainless Steel with Touchpad

iKey's stainless steel panel mount keyboards are durable, cleanable and easily customized to fit the unique demands of its application. The PM-65-TP-SS integrates an industrial touchpad for controlled usability. For public display kiosks, these features create a waterproof, environmentally durable solution perfect for harsh kiosk implementations. Because most kiosks do not require supervision by operators or retailers, these products help prevent theft and damage by vandals through stainless steel keys, an easily mountable design and unparalleled durability.



Technical Specifications

Certifications Meets or exceeds: IEC 60512-6 IEC 60512-4 IP65 FCC Part 15, Class B

Shock 3 x 11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 7' straight

Key Switch MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION

FORCE: 6.35 oz. +/- 0.70 oz. (180g +/- 20g)

Vibration POWER SPECTRAL DENSITY: 0.04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3

hours

Power KEYBOARD: 5V@20ma (from CPU port) TOUCHPAD: 5V@10ma (from mouse connection port)

Compatability USB KEYBOARD: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C(-40F to +194F) OPERATING: -40C to +60C (-40F to +140F)

Weight 4..00 lbs +/- 0.10 lbs (1.84 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 16.25" x 5.11" x 1.25" (w-h-d) 412.8mm x 129.8mm x 31.8mm CUTOUT: 15.76" x 4.62" (w-h) 400.3mm x 117.3 mm

Model Numbers PM-65-TP-SS-USB

Features and Benefits

• 10-Year Lifespan • Integrated Touchpad

Integrated, programmable function keys
Low-profile stainless steel keys

Vandal Proof design