

SB-101

ULTRA-THIN KEYBOARD WITH QUICKLOCK?

The SB-101 is one of the thinnest keyboards to date with a depth less than half an inch. Featuring a QuickLock? key, the SB-101 can be disabled quickly to avoid unwanted keystrokes during the cleaning and disinfection process. Built for versatility, the SB-101 features individually lit red LED backlit keys for nighttime or ambient light use and comes in a fully-sealed polycarbonate case with rubber keypad. The SB-101's ultra-thin design and cleaning capabilities make it an ideal solution for use in small spaces, vehicles, forklifts, and rackdrawers. Optional magnetic mounting is available. To learn more, visit our SB-101 video on YouTube's iKey KeyBoard Channel: Click Here Features: QuickLock? Industrial Silicone Rubber Keypad Lightweight ABS Polycarbonate Case Meets NEMA 4X (IP65) Specifications Red LED Backlit Keys USB Connectivity Shallow Depth Ultra-Thin Design

Product Code SB-101

| CERTIFICATIONS | NEMA 4X, IP65, UL90650, FCC Part 15 Class B |
|-------------------|---|
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 10' straight (3 m) Single-Cable USB |
| KEY SWITCH | MATERIAL: industrial silicone rubber LIFE: greater than 10 million cycles TRAVEL: 0.055 in. |
| | (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with |
| | mechanical snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF |
| | TEST PER AXIS: 3 hours |
| POWER | KEYBOARD: 200mA @ 5V (from CPU port) |
| COMPATIBILITY | USB KEYBOARD: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F) |
| WEIGHT | 1.2 lbs +/- 0.10lbs (0.54 kg +/- 0.05 kg) |
| WARRANTY | 1 Year Limited Warranty |
| DIMENSIONS | 14.94" x 5.89" x 0.60" (w-h-d) 379.5mm x 149.6mm x 15.2mm |
| MODEL NUMBERS | SB-101-USB (with USB cable) |
| | |