

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

www.ikey.com

SK-101-M

Mobile Keyboard with Numeric Keypad

iKey's SlimKey™ SK-101-M keyboard provides full-sized versatility in a rugged, c ompact design. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SlimKey™ SK-101-M is ideal for use in environments ranging f rom manufacturing to material handling. The large numeric pad on the SK-101-M allows for easy data entry, while its robust polycarbonate case stands up to the roughest of conditions.



Technical Specifications

Certifications NEMA 4X UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10' straight (3 m)

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05

oz +/- 1.06 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power PS/2: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port)

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB

Compatability PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 2 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 14.50" x 5.50" x 1.56" (w-h-d) 368.3mm x 139.7mm x 39.6mm

Features and Benefits

12 Function Keys

Built-In Mounting Holes

Large, 10-Key Numeric Pad

• MS Windows Function Keys

· Slim, Compact Design

• USB and PS/2 configurations available

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800- 866-6506