

SL-86-911-TP

Mountable Keyboard with Touchpad

The SL-86-911-TP keyboard is designed for vehicle mount in emergency, police, service, transport trucks and marine vessels. Features include a user-friendly integrated touchpad, backlit keys for low-light environments, a one-touch emergency key and mounting holes. The new, easy-to-use integrated touchpad was created to meet public demand for a user-friendly alternative to the traditional HulaPoint™ device.



Technical Specifications

| | |
|-------------------|--|
| Certifications | NEMA 4X, CE UL60950, FCC Part 15 Class B |
| Shock | 3x11 ms pulses of 50g on each of 3 axes |
| Cable | LENGTH: 4 ft coiled (1.2m) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB |
| Key Switch | MATERIAL: Industrial Silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap |
| Vibration | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours |
| Power | PS/2: KEYBOARD: 200mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 210mA@5V (from CPU port) |
| Compatibility | PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS |
| Temperature Range | Storage -40C to +90C (-40F to +194F) Operating -40C to +70C (-40F to +158F) |
| Weight | 2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg) |
| Warranty | 1 Year Limited Warranty |
| Humidity | 100% Humidity Resistant |
| Dimensions | 11.39" x 7.30" x 1.87" (w-h-d) 289.56mm x 185.42mm x 47.24mm |
| Model Numbers | SL-86-911-TP-PS2: With PS/2 cable SL-86-911-TP-USB: With USB cable |

Features and Benefits

- One-Touch Emergency Key
- PS/2 or USB configurations available