2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

www.ikey.com

SL-86-911

Industrial Keyboard with Emergency Key

The SL-86-911 offers a rugged keyboard and a rugged computer pointing device in one compact package. Ideal for public safety applications, it features a specially designed emergency key and red LED backlit keys. The SL-86-911 integrates the HulaPoint II™, an upgraded pointing device that offers improved s ensitivity and increased durability. Featuring a compact design with mounting holes, the SL-86-911 fits securely in a vehicle's console to serve effectively as a mobile application. It boasts a completely sealed and ruggedized construction that allows it to meet NEMA 4X specifications, ensuring that this keyboard is sealed against the elements or unwanted spills.



Technical Specifications

Certifications NEMA 4X, CE UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 4 ft coiled (1.2 meters) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-

Cable USB

Key Switch MATERIAL: Industrial silicone rubber LIFE: Greater Than 10 million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION

FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power PS/2: KEYBOARD: 200mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouse port) USB: 235mA@5V (from

CPU port

Compatability PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and

Macintosh OS

Temperature Range STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)

Weight 2 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Dimensions 11.40" x 6.30" x 1.86" (w-h-d) 289.6mm x 160.0mm x 47.2mm

100% Humidity Resistant

Model Numbers

Humidity

Features and Benefits

12 Function Keys

86-Key Functionality

• AT/Serial, PS/2 and USB or configurations available

Integrated Backlighting

• Integrated HulaPoint II Pointing Device

One-Touch Emergency Key