

SL-88-OEM

OEM Compact Backlit Industrial Keyboard

The SL-88-OEM, when properly installed, is designed to meet NEMA 4X specifications and is ideal for industrial, kiosk and mobile computing applications. It is a compact keyboard featuring red LED backlit keys and an industrial silicone rubber keypad. The SL-88-OEM has a secondary legend accessed with the NumLock and Fn key.



Technical Specifications

Certifications	NEMA 4X, CE UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10' straight (3 m)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from USB port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
Compatability	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C OPERATING: -40C to +70C
Weight	1 lbs (0.45 kg)
Warranty	90 day limited warranty
Humidity	100% (when properly installed)
Dimensions	11.12" x 6.05" x 0.72" (w-h-d) 282.5mm x 153.7mm x 18.3mm
Model Numbers	

Features and Benefits

- 12 Function Keys
- 88-Key Functionality
- Integrated Backlighting
- USB and PS/2 configurations available