2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

www.ikey.com

SLP-101

Full-Size Panel Mount Keyboard with Backlighting

iKey's SlimKey[™] SLP-101 panel mount keyboard provides full-size versatility in a r ugged, compact design. It features red LED backlighting for low-light environments. When properly installed, the SlimKey[™] SLP-101 is engineered for N EMA 4X protection from dust, water and corrosive liquids. It is designed for easy integration into workstations, kiosks and industrial environments. The large numeric pad on the SLP-101 allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions.

Technical Specifications

Certifications NEMA 4X, CE UL 60950, FCC Part 15 Class B

Shock 3 X 11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10' straight (3 m) DESIGN: "Y" PS/2 or USB Cable

Key Switch MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION

FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap

Vibration Vibration POWER SPECTRAL DENSITY: .04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER

AXIS: 3 hours

Power PS2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port)

Compatability PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)

Warranty 1 Year Limited Warranty

Humidity 100% Humidity Resistant

Dimensions 15.10" x 6.05" x 0.58" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (w-h-d) 383.5mm x 153.7mm x 153.7mm x 14.7mm SCREWS: 0.50" (w-h-d) 383.5mm x 153.7mm x

h) 348mm x 118.1mm

Model Numbers SLP-101-PS2: With PS/2 cable SLP-101-USB: With USB cable

Features and Benefits

· ABS Polycarbonate Frame

· Cleanable, Liquidproof Design

• Industrial Silicone Rubber Keypad

• PS/2 or USB configurations available

Red Backlit Keys