


uHP-1535

Industrial HulaPoint™ Pointing Device

The uHP-1535 is a smaller version of our regular HulaPoint™. The two-button device offers the versatility and convenience of the HulaPoint™ but in a compact version to suit the needs of industrial laptops and workstations. Like all of iKey's products, the sealed design means the uHP-1535 is dustproof, waterproof and non-corrosive.



Technical Specifications

Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 6ft (1.8 m)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2 HULAPOINT: 5V@ 10 ma (from mouse conn. port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB
Compatability	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems SERIAL HULAPOINT: All Windows Operating Systems
Temperature Range	STORAGE: -40C to +90C OPERATING: -40C to +70C
Weight	1 lb (.46 kg)
Warranty	90 day limited warranty
Humidity	100% (when properly installed)
Dimensions	3.5" x 1.5" x 0.5" (w-h-d)

Features and Benefits

- AT/Serial and PS/2 configurations available
- OEM Kit: PCB, rubber overlay, and cable